

Cisco

300-710 Exam

Securing Networks with Cisco Firepower

Questions & Answers

Demo

Version: 21.0

Topic 1, Deployment

Question: 1

What is a result of enabling Cisco FTD clustering?

- A. For the dynamic routing feature, if the master unit fails, the newly elected master unit maintains all existing connections.
- B. Integrated Routing and Bridging is supported on the master unit.
- C. Site-to-site VPN functionality is limited to the master unit, and all VPN connections are dropped if the master unit fails.
- D. All Firepower appliances can support Cisco FTD clustering.

Answer: C

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/security/firepower/640/configuration/guide/fpmc-config-guide-v64/clustering_for_the_firepower_threat_defense.html

Question: 2

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/security/firepower-management-center/212699-configure-ftd-high-availability-on-firep.html>

Question: 3

On the advanced tab under inline set properties, which allows interfaces to emulate a passive interface?

- A. transparent inline mode
- B. TAP mode
- C. strict TCP enforcement
- D. propagate link state

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/security/firepower/640/configuration/guide/fpmc-config-guide-v64/inline_sets_and_passive_interfaces_for_firepower_threat_defense.html

Question: 4

What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/security/firepower/650/configuration/guide/fpmc-config-guide-v65/ips_device_deployments_and_configuration.html

Question: 5

What is the difference between inline and inline tap on Cisco Firepower?

- A. Inline tap mode can send a copy of the traffic to another device.
- B. Inline tap mode does full packet capture.
- C. Inline mode cannot do SSL decryption.
- D. Inline mode can drop malicious traffic.

Answer: A

Explanation:

Thank You For Trying 300-710 PDF Demo

To try our 300-710 Premium Files visit link below:

<https://examsland.com/latest-exam-questions/300-710/>

Start Your 300-710 Preparation

Use Coupon **EL25 for extra 25% discount on the purchase of Practice Test Software.**