

Implementing and Configuring Cisco Identity Services Engine Questions & Answers Demo

A. by enabling 802.1AE on every network device

B. by the Security Group Tag Exchange Protocol

C. by embedding the security group tag in the IP header

D. by embedding the security group tag in the 802.1Q header

Version: 26.1

Question: 1	
What are two components of the posture requirement when configuring Cisc	co ISE posture? (Choose two)
A. updates	
B. remediation actions	
C. Client Provisioning portal	
D. conditions	
E. access policy	
- Contanting	Answer: B, D
Explanation:	
Question: 2	
What is a method for transporting security group tags throughout the netwo	rk?

			Answer: B
Explanation:			
Question: 3			
Which two ports must be open ISE? (Choose two).	between Cisco ISE and	the client when you c	configure posture on Cisco
A. TCP 8443			
B. TCP 8906			
C. TCP 443			
D. TCP 80			
E. TCP 8905			
		_	Answer: A, E
Explanation:			7.11.5Weii 71, E
Question: 4			
Question 4			
Which profiling probe collects th	ne user-agent string?		
A. DHCP			
B. AD			
C. HTTP			

D. NMAP		
Explanation:		Answer: C
Question: 5		
Which supplicant(s) and serve	er(s) are capable of supporting EAP-CHAINING?	
A. Cisco AnyConnect NAM an	d Cisco Identity Service Engine	
B. Cisco AnyConnect NAM an	d Cisco Access Control Server	
C. Cisco Secure Services Clien	t and Cisco Access Control Server	
D. Windows Native Supplican	t and Cisco Identity Service Engine	
Explanation:		Answer: A

Thank You For Trying 300-715 PDF Demo

To try our 300-715 Premium Files visit link below:

https://examsland.com/latest-exam-questions/300-715/

Start Your 300-715 Preparation

Use Coupon EL25 for extra 25% discount on the purchase of Practice Test Software.