

Cisco

Exam 650-472

Introduction to 802.1X Operations for Cisco Security Professionals Exam

Version: Demo

[Total Questions: 10]

Question No : 1

Which protocol used to communicate between the authenticator and authentication server?

- A. RADIUS
- B. EAP-FAST
- C. EAPOL
- D. EAP-TLS
- E. PEAP

Answer: A

Question No : 2

Which statement correctly defines a persona?

- A. A Cisco ISE node can be configured as a primary or backup persona.
- B. Persona refers to collections of services running on a Cisco ISE node.
- C. A Cisco ISE node can be configured as a wired or wireless persona.
- D. Persona relates to the collection of 802.1X services configured on a Cisco Catalyst switch.
- E. Persona refers to the collection of EAP methods available to a supplicant.
- F. A Cisco ISE node can be configured as a standalone or distributed persona.

Answer: B

Question No : 3

Which two choices are drivers of IEEE 802.1X adoption? (Choose two.)

- A. Guest networks
- B. Heterogeneous Networks
- C. Pervasive Wireless Deployments
- D. Unprotected switch ports
- E. Limited 802.1X standard functionality

Answer: A,C

Question No : 4

What is the purpose of the guest VLAN on a Cisco Catalyst switch?

- A. It provides configurable guest access to devices that have a supplicant but lack local credentials.
- B. It provides configurable guest access to non-supplicant devices that lack local credentials.
- C. It provides configurable guest access to devices that have a supplicant when the authenticator is down or unreachable.
- D. It provides configurable guest access to non-supplicant devices that have local credentials.
- E. It provides configurable guest access to devices that have a supplicant when the authentication server is down or unreachable.

Answer: B

Question No : 5

Which module is NOT a valid component of Cisco AnyConnect Secure Mobility Client for Windows?

- A. VPN Module
- B. Profiling Module
- C. Network Access Manager
- D. Telemetry Module

Answer: B

Explanation:

These are the VPN modules in Cisco Anyconnect client:

Network Access Manager

Posture Module

Telemetry Module

WebSecurity Module

Question No : 6

Which two choices are valid methods of authorizing a wired supplicant? (Choose two.)

- A. EAP-FAST
- B. VLAN assignment
- C. dACL
- D. EAPOL
- E. RADIUS

Answer: B,C

Question No : 7

Which two elements must you configure on a Cisco Wireless LAN Controller to allow Cisco ISE to authenticate wireless users? (Choose two.)

- A. Configure each WLAN to use the configured Cisco ISE node.
- B. Configure all attached LWAPs to use the configured Cisco ISE node.
- C. Configure the WLC to join a Microsoft Active Directory domain.
- D. Configure Cisco ISE as a RADIUS accounting server and shared secret.
- E. Configure Cisco ISE as a RADIUS authentication server and shared secret.
- F. Configure RADIUS attributes for each SSID.

Answer: A,E

Question No : 8

Which two of these partial Cisco Catalyst switch commands are used to configure FlexAuth? (Choose two)

- A. 3k-access(config-if)# authentication order
- B. 3k-access(config-if)# authentication priority
- C. 3k-access(config-rf)# authentication fallback
- D. 3k-access(config)# authentication direction
- E. 3k-access(config)# authentication priority
- F. 3k-access (config-rf) # authentication direction
- G. 3k-access (config) # authentication order
- H. 3k-access (config) #authentication fallback

Answer: A,B

Question No : 9

What is the default username and password for Cisco ISE?

- A. Admin/admin
- B. Cisco/Cisco
- C. Admin/Cisco
- D. Administrator/ Cisco
- E. Administrator/Admin
- F. Cisco/Cisco123
- G. Admin/Cisco 123
- H. Administrator/ Cisco 123

Answer: C

Question No : 10

Which two statements are true regarding communication from the authenticator to the authentication server (Cisco ISE)? (Choose two.)

- A. EAP messages are sent encapsulated in RADIUS protocol over UDP port 1645.
- B. EAP messages are sent encapsulated in RADIUS protocol over UDP port 1812.
- C. EAP messages are sent to the RADIUS server over UDP port 1812.
- D. EAP messages are sent to the RADIUS server over UDP port 1646.
- E. EAP messages are sent encapsulated in RADIUS protocol over UDP port 1646.
- F. EAP messages are sent to the RADIUS server over UDP port 1645.

Answer: A,B

Thank You For Trying 650-472 PDF Demo

To try our 650-472 Premium Files visit link below:

<https://examsland.com/latest-exam-questions/650-472/>

Start Your 650-472 Preparation

Use Coupon **EL25 for extra 25% discount on the purchase of Practice Test Software.**