

Certified Specialist in Advanced Automation: Ansible Best Practices

Version: 4.0

Question: 1

Install and configure ansible

User bob has been created on your control node. Give him the appropriate permissions on the control node. Install the necessary packages to run ansible on the control node.

Create a configuration file /home/bob/ansible/ansible.cfg to meet the following requirements:

- The roles path should include /home/bob/ansible/roles, as well as any other path that may be required for the course of the sample exam.
- The inventory file path is /home/bob/ansible/inventory.
- Ansible should be able to manage 10 hosts at a single time.
- Ansible should connect to all managed nodes using the bob user.

Create an inventory file for the following five nodes:

nodel.example.com node2.example.com node3.example.com node4.example.com node5.example.com

Configure these nodes to be in an inventory file where node1 is a member of group dev. nodc2 is a member of group test, nodc3 is a member of group proxy, nodc4 and node 5 are members of group prod. Also, prod is a member of group webservers.

Answer: A

A. Explanation: In/home/sandy/ansible/ansible.cfg [defaults] inventory=/home/sandy/ansible/inventory roles_path=/home/sandy/ansible/roles remote_user= sandy host_key_checking=false [privilegeescalation] become=true become_user=root become_method=sudo become ask pass=false

In /home/sandy/ansible/inventory

Page 3

[dev] node 1 .<u>example.com</u> [test] <u>node2.example.com</u> [proxy] node3 .<u>example.com</u> [prod] <u>node4.example.com</u> [webservers:children] prod

Question: 2

Create a file called adhoc.sh in /home/sandy/ansible which will use adhoc commands to set up a new repository. The name of the repo will be 'EPEL' the description 'RHEL8' the baseurl is <u>'https://dl.fedoraproject.org/pub/epel/epel-release-latest-8.noarch.rmp'</u> there is no gpgcheck, but you should enable the repo.

* You should be able to use an bash script using adhoc commands to enable repos. Depending on your lab setup, you may need to make this repo "state=absent" after you pass this task.

Answer: A

A. Explanation: chmod 0777 adhoc.sh vim adhoc.sh #I/bin/bash ansible all -m yum_repository -a 'name=EPEL description=RHEL8 baseurl=<u>https://dl.fedoraproject.org/pub/epel/epel-release-latest-8.noarch.rmp</u> gpgcheck=no enabled=yes'

Question: 3

Create a file called packages.yml in /home/sandy/ansible to install some packages for the following hosts. On dev, prod and webservers install packages httpd, mod_ssl, and mariadb. On dev only install the development tools package. Also, on dev host update all the packages to the latest.

Answer: A

A. Explanation: Solution as:

https://www.braindumpsstore.com

```
name: install pack
hosts: dev,test,webservers
become: true
tasks:
  - name: install on all hosts in this play
    yum:
      name:

    httpd

        - mod ssl
        - mariadb
      state: latest
  - name: install on dev only
    yum:
      name:

    '@Development tools'

      state: latest
    when: "dev" in group_names
```

** NOTE 1 a more acceptable answer is likely 'present' since it's not asking to install the latest state: present

** NOTE 2 need to update the development node

- name: update all packages on development node

yum: name: '*' state: latest

Question: 4

Create a role called sample-apache in /home/sandy/ansible/roles that enables and starts httpd, enables and starts the firewall and allows the webserver service. Create a template called index.html.j2 which creates and serves a message from /var/www/html/index.html Whenever the content of the file changes, restart the webserver service.

Welcome to [FQDN] on [IP]

Replace the FQDN with the fully qualified domain name and IP with the ip address of the node using ansible facts. Lastly, create a playbook in /home/sandy/ansible/ called apache.yml and use the role to serve the index file on webserver hosts.

Answer: A

A. Explanation: /home/sandy/ansible/apache.yml

https://www.braindumpsstore.com



/home/sandy/ansible/roles/sample-apache/tasks/main.yml

Page 6

```
tasks file for sample-apache
name: enable httpd
service:
  name: httpd
  state: started
  enabled: true
name: enable firewall
service:
  name: firewalld
  state: started
  enabled: true
name: firewall http service
firewalld:
  service: http
  state: enabled
  permanent: yes
  immediate: yes
name: index
template:
  src: templates/index.html.j2
  dest: /var/www/html/index.html
notify:

restart
```

/home/sandy/ansible/roles/sample-apache/templates/index.html.j2
Welcome to {{ansible_fqdn}} {{ansible_default_ipv4.address}}
In /home/sandy/ansible/roles/sample-apache/handlers/main.yml
- name: restart
 service:
 name: httpd
 state: restarted

https://www.braindumpsstore.com

Question: 5

Create a file called requirements.yml in /home/sandy/ansible/roles to install two roles. The source for the first role is geerlingguy.haproxy and geerlingguy.php. Name the first haproxy-role and the second php-role. The roles should be installed in /home/sandy/ansible/roles.

Answer: A

A. Explanation:

in /home/sandy/ansible/roles vim requirements.yml

src: geerlingguy.haproxy
name: haproxy-role
src: geerlingguy. php_role
name: php_role

Run the requirements file from the roles directory: ansible-galaxy install -r requirements.yml -p /home/sandy/ansible/roles

Thank You for trying EX447 PDF Demo

To try our EX447 practice exam software visit link below

https://www.braindumpsstore.com/EX447.html

Start Your EX447 Preparation

[Limited Time Offer] Use Coupon "20OFF" for special 20% discount on your purchase. Test your EX447 preparation with actual exam questions.

Thank You For Trying EX447 PDF Demo

To try our EX447 Premium Files visit link below:

https://examsland.com/latest-exam-questions/EX447/

Start Your EX447 Preparation

Use Coupon EL25 for extra 25% discount on the purchase of Practice Test Software.