

## **Huawei Certified Network Professional-Access Network Exam**

Questions & Answers Demo

## Version: 9.0

Question: 1	
(single) When the MA5680T traffic is scheduled, which of the follo	wing traffic will be marked as red?
A. Traffic below CIR B. Traffic above CIR but below PIR C. Traffic above PIR D. Traffic above CBS	Answer: C
Question: 2	
(single) Is the following description correct? Under IGMP snooping, two users on the OLT broadcast the same join messages to the multicast router.	e program, and the OLT sends two
A. True B. False	
	Answer: A
Question: 3	
( Single) What is the command to support local loopback on the I	MA5600 ADSL port?
A. Loopback B. loop-detect C. atm-ping D. ring check	
	Answer: A
Question: 4	

(single) After installing the sybase patch, which of the following commands can display the version information of the sybase patch that has been installed?

- A. 1>select @@version2>go
- B. 1>select @@patch2>go

C. 1>version_help2>go D. 1>ver_help2>go			
			Answer: A
Question: 5			
(single) Is the following description The minimum activation rate the minimum activation rate to setting is too large, the moden	Minimum transmissio hat must be reached i	n this direction aft	•
A. True B. False			
			Answer: A
Question: 6			
(single) MA5680T in the tenth configure?	mplate mode, tcont,	gemport configu	ration integration where to
A. ont-srvpmfile B. ont-linepmfile C. ont-profile D. dba-profile			
			Answer: B
Question: 7			
(multiple) If the MA5680T frestarting), usually we can use What kind of uploading methors upgrade?	the BIOS upgrade met	hod to end.	
A. ftp B. tftp C. Xmodem D. wftp			
·			Answer: ABC
			Allowell Abe
Question: 8			

(single) Is the following description correct?

either auto-negotiation mode or mandatory mode.	
A. True B. False	
	Answer: B
Question: 9	
(single) Which of the following products in the GPON network does not	belong to the MDU series?
A. MA5616 B. MA5612 C. MA5620G D. MA5680T	
	Answer: D
Question: 10	
Is the description under (single) correct? When a multicast service is configured, the VLAN carrying the multicas the id of the unicast VLAN.	at service must be the same as
A. True B. False	
	Answer: B
Question: 11	
(single) By default, which type of queue scheduling mode is on the MAS	5600T/MA5680T?
A. WRR B. PQ C. WFQ D. CQ	
	Answer: B
Question: 12	

The MSAN is connected to the lanswitch GE or the FE. The working mode of the two ports can be

(single) According to the IEEE 802.1Q standard, where is the VLAN identification field in the Ethernet frame?

A. Source MAC address and destination MAC address before

(single) All H.248 commands must be sent back by the receiver. Which of the following is used to indicate a response message?

B. Between the source MAC address and the destination MAC address C. After the source MAC address and the destination MAC address	
D. Not fixed	
	Answer: C
Question: 13	
(single) Is the following description correct? The MA5600T/MA5680T supports Ethernet, E1, and POTS services o support ATM services.	n the PON side and does not
A. True B. False	
	Answer: A
Question: 14	
(single) Is the following description correct?  The ADSL PPPoE/PPPoA user of the MA5600 implements authenticate After the opening, there is often a business interruption, but after the to achieve Internet access. This problem may be caused by incorrect in of port parameters.  A. True  B. False	interruption, it can be redialed
	Answer: A
Question: 15  (multiple) MA5600T acceptance test manual What are the categories of	of acceptance test items?
A. Foundation package B. Advanced package C. Extension Pack A D. Expansion Pack B	
	Answer: ACD
Question: 16	

A. request	
B. pending C. ack	
D. complete	
2. cep.c.c	
	Answer: B
Question: 17	
(single) Is the following description correct?  The level of the MA5600T alarm can be divided into five levels: critical cleared.	, major, minor, warning, and
A. True B. False	
	Answer: A
Question: 18	
(single) When locating ADSL/ADSL2+ failure, which of the following remake a call but not to access the Internet?	asons may cause the user to
<ul> <li>A. Line configuration template interleaving depth configuration is unreas</li> <li>B. ADSL Modem failure</li> <li>C. User external line interruption</li> <li>D. None of the above</li> </ul>	sonable
	Answer: B
Question: 19	
(multiple) When the ADSL/ADSL2+ line is in good condition, what parato increase the transmission rate?	meters can be tried to adjust
A. The port channel mode is changed to "fast"	
B. The port channel mode is changed to "interlace" and the interleaving	delay is increased.
C. Reduce target noise margin	
D. Improve target noise margin	
	Answer: AC
Question: 20	

Is the description under (single) correct?

**Answer: A** 

The GPON system inherits the TDM signal. The essence of the TDM signal is to encapsulate the TDM
into a GEM frame on the ONU. The GEM frame is decapsulated into a TDM signal on the OLT, and
then transmitted to the device capable of transmitting the TDM signal.

Answer: A
port of the MA5680T is only

## Thank You For Trying H35-211 PDF Demo

To try our H35-211 Premium Files visit link below:

https://examsland.com/latest-exam-questions/H35-211/

**Start Your H35-211 Preparation** 

Use Coupon EL25 for extra 25% discount on the purchase of Practice Test Software.