

## Huawei H35-561 HCIP LTE RNP&RNO V1.0 Questions & Answers

Demo

## Version: 5.0

Question: 1		
Which of the following events	can be used to trigger inter-frequency switch	ing? (multiple choice)
A. A2		
B. A3		
C. A4		
D. A5		
		Answer: B, C, D
Question: 2		
How many types of TDD uplin	k and downlink subframe configurations are th	nere?
A. 3		
B. 5		
C. 7		
D. 9		
		Answer: C
Question: 3		
When X2 handover cannot be	performed between eNodeBs, S1 handover is	performed.
A. True		
B. False		
		Answer: A
Question: 4		
How many configurations are	there for R8 TDD special subframe configuration	on?
A. 3		

B. 5 C. 7

<b>–</b>	9
----------	---

Answer: D
-----------

## **Question: 5**

In which of the following messages will the tracking area information be sent to the MME for consistency check?

A. S1AP: E-RAB setup requestB. RRC: RRC connection requestC. S1AP: Initil context setup request

D. S1AP: S1 setup request

Answer: D

## Thank You For Trying H35-561 PDF Demo

To try our H35-561 Premium Files visit link below:

https://examsland.com/latest-exam-questions/H35-561/

**Start Your H35-561 Preparation** 

Use Coupon EL25 for extra 25% discount on the purchase of Practice Test Software.