

# **Salesforce**

## **JAVASCRIPT-DEVELOPER-I Exam**

### **Salesforce Certified JavaScript Developer I**

#### **Questions & Answers Demo**

## Version: 12.2

---

### Question: 1

---

Refer to the code below:

```
01 const exec = (item, delay) =>{
02 new Promise(resolve => setTimeout( () => resolve(item), delay)),
03 async function runParallel() {
04 Const (result1, result2, result3) = await Promise.all{
05 [exec ('x', '100') , exec('y', 500), exec('z', '100')]
06 };07 return `parallel is done: ${result1} ${result2}${result3}`;
08 }}
```

Which two statements correctly execute the runParallel () function?

Choose 2 answers

- A. Async runParallel () .then(data);
- B. runParallel ( ). done(function(data){  
return data;});
- C. runParallel () .then(data);
- D. runParallel () .then(function(data)  
return data

---

**Answer: B, D**

---

Explanation:

---

### Question: 2

---

A developer needs to test this function:

```
01 const sum3 = (arr) => (
02 if (!arr.length) return 0,
03 if (arr.length === 1) return arr[0],
04 if (arr.length === 2) return arr[0] + arr[1],
05 return arr[0] + arr[1] + arr[2],
06 );
```

Which two assert statements are valid tests for the function?

Choose 2 answers

- A. console.assert(sum3(1, '2')) == 12);
- B. console.assert(sum3(0)) == 0);
- C. console.assert(sum3(-3, 2 )) == -1);

D. console.assert(sum3('hello', 2, 3, 4)) === NaN);

---

**Answer: A, C**

---

Explanation:

---

**Question: 3**

---

Which statement phrases successfully?

- A. JSON.parse ( ' foo ' );
- B. JSON.parse ( " foo " );
- C. JSON.parse( " ' foo ' " );
- D. JSON.parse(' " foo " ');

---

**Answer: D**

---

Explanation:

---

**Question: 4**

---

Refer to the code below:

```
01 let car1 = new promise( (_, reject) =>
02   setTimeout(reject, 2000, "Car 1 crashed in"));
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, "Car 2
completed"));
04 let car3 = new Promise(resolve => setTimeout (resolve, 3000, "Car 3
Completed"));
05 Promise.race([car1, car2, car3])
06 .then(value => (
07   let result = $(value) the race. `;
08 ))
09 .catch( arr => (
10   console.log("Race is cancelled.", err);
11 ));
```

What is the value of result when Promise.race executes?

- A. Car 3 completed the race.
- B. Car 1 crashed in the race.
- C. Car 2 completed the race.
- D. Race is cancelled.

---

**Answer: C**

---

Explanation:

---

### Question: 5

---

Refer to the code below:

```
for(let number =2 ; number <= 5 ; number += 1 ) {  
  // insert code statement here  
}
```

The developer needs to insert a code statement in the location shown. The code statement has these requirements:

1. Does require an import
2. Logs an error when the boolean statement evaluates to false
3. Works in both the browser and Node.js

Which meet the requirements?

- A. `assert (number % 2 === 0);`
- B. `console.error(number % 2 === 0);`
- C. `console.debug(number % 2 === 0);`
- D. `console.assert(number % 2 === 0);`

---

**Answer: B**

---

## Thank You For Trying Javascript-Developer-I PDF Demo

To try our Javascript-Developer-I Premium Files visit link below:

<https://examsland.com/latest-exam-questions/Javascript-Developer-I/>

**Start Your Javascript-Developer-I Preparation**

Use Coupon **EL25** for extra 25% discount on the purchase of Practice Test Software.