McAfee

MA0-101 Exam

McAfee Certified Product Specialist- NSP Exam

Questions & Answers
Demo

Question: 1

Which port needs to be opened for Alert Channel communication between Sensor and Manager through a firewall?

A. 8501
B. 8502
C. 8503
D. 8555

Answer: B

Question: 2

Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method?

A. Signature based
B. Pattern matching
C. Denial of Service
D. Remediation

Answer: C

Question: 3

Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?

A. sensor perf-debug 100
B. sensor perf-debug on 100
C. sensor perf-debug Interface all 100
D. sensor perf-debug assert 100

Answer: A

Question: 4

Page 3

ExamsLand provides 100% free McAfee MA0-101 practice questions and answers in pdf. Instant access.

What type of encryption is used for file transfers between the Sensor and the Manager?

A. SSL with RC4
B. SSL with MD5
C. SSL with RC4 and MD5
D. DES

Answer: D

Question: 5

When placed in Layer3 mode, a Sensor detects a Layer2 device based on which of the following?

A. MAC address
B. IP address
C. DNS
D. Subnet

Answer: B

Question: 6

What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?

A. arp spoof status
B. arp spoof enable
C. arp dump
D. arp flush

Answer: C

Question: 7

DoS detection is implemented in which of the following modes? (Choose two)

A. Learning mode
B. Configuration mode
C. Threshold mode
D. Bidirectional mode

Page 4

ExamsLand provides 100% free McAfee MA0-101 practice questions and answers in pdf. Instant access.

E. Inbound mode

Answer: A, C

Question: 8

Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

A. 8501
B. 8502
C. 8503
D. 8555

Answer: C

Question: 9

Which port is correctly defined for the Alert Channel on the Network Security Manager?

A. 8500
B. 8501
C. 8502
D. 8504

Answer: C

Question: 10

In double VLAN tagging, a second VLAN tag that is inserted into the frame is referred to as which of the following?

A. Customer Identification tag (CD)
B. VLAN Identification tag (VID)
C. Outer Identification tag (OID)
D. Inner Identification tag (HD)

Answer: A

Thank You For Trying MA0-101 PDF Demo

To try our MA0-101 Premium Files visit link below:

https://examsland.com/latest-exam-questions/MA0-101/

Start Your MA0-101 Preparation

Use Coupon EL25 for extra 25% discount on the purchase of Practice Test Software.