

# **NetApp**

## **NS0-181 Exam**

**NetApp Certified Storage Installation Engineer, ONTAP Exam**

### **Questions & Answers Demo**

## Version: 8.1

---

### Question: 1

---

A customer wants to reduce the disk allocation requirement for the root aggregate and increase usable storage by partitioning the disks into one large part and one small part. The small part is used for the root aggregate and the large part for the data aggregates.

In this situation, what is this feature called?

- A. ONTAP
- B. storage virtual machine
- C. Advanced Drive Partitioning
- D. RAID

---

**Answer: A**

---

<https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-concepts%2FGUID-B745CFA8-2C4C-47F1-A984-B95D3EBCAAB4.html>

---

### Question: 2

---

A customer has a new 2-node ONTAP system. They have configured the cluster for iSCSI and LUN access.

Which two statements are correct in this scenario? (Choose two.)

- A. In a case of a node error, the broadcast domain will automatically be moved to the surviving node.
- B. Create a single failover group with both nodes' ports, e0M and e0i, applied to each node iSCSI
- C. A best practice is to have at least one UF per node per SVM for iSCSI access.
- D. Use Asymmetric Logical Unit Assignment (ALUA), igroups and host-side multipath Input/output (MPIO) for path management and resiliency with iSCSI.

---

**Answer: AB**

---

---

### Question: 3

---

Starting with ONTAP 9.1, what is the maximum number of HA pairs that are supported when using a SAN cluster?

- A. 4
- B. 2
- C. 6
- D. 8

---

**Answer: A**

---

---

**Question: 4**

---

What is a valid failover policy for a SAN LIF?

- A. disabled
- B. broadcast-domain-wide
- C. system-define
- D. local-only

---

**Answer: B**

---

<https://library.netapp.com/ecmdocs/ECMP1636021/html/GUID-D99400AB-789A-4F6A-8443-9F74165F2B88.html>

---

**Question: 5**

---

You are adding two new nodes into an existing switchless 2-node cluster. Which two statements are true in this scenario? (Choose two.)

- A. You first need to install the cluster interconnect switches to the existing cluster.
- B. You must make sure that the existing nodes are healthy and that all cluster links are up.
- C. The existing cluster must use clustered Data ONTAP 8.1 or later software.
- D. You need to schedule downtime to add these two nodes.

---

**Answer: AB**

---

<https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-sag%2FGUID-B13FF812-785E-4E62-9914-30E7A8F51A4C.html>

---

**Question: 6**

---

Your customer has filled out the customer installation worksheet. However, the customer's network environment is not set up and ready for the new ONTAP 9.1 system. The customer requests that you install the system and states that they will finish the configuration when they have acquired the appropriate network connections.

Which two statements are correct about this scenario? (Choose two.)

- A. You should cable a cluster so that the cluster interconnect traffic is on a separate network from all other traffic.
- B. You cannot install an ONTAP system without having the customer network configuration.
- C. You should cable all of the controllers and disk shelves, power on the system, and then leave the system as-is for the customer to configure.
- D. A cluster can be created without data network connections, but it must include a cluster interconnect connection.

---

**Answer: BD**

---

**Thank You For Trying NS0-181 PDF Demo**

**To try our NS0-181 Premium Files visit link below:**

**<https://examsland.com/latest-exam-questions/NS0-181/>**

**Start Your NS0-181 Preparation**

**Use Coupon **EL25** for extra 25% discount on the purchase of Practice Test Software.**